

CAMSO SKS 793S



SKID STEER
LOADERS



SEVERE-DUTY AND FLAT-FREE

Next-generation versatile solid tire solution. Engineered to deliver excellent ride quality and best durability for mixed- and hard surface skid steer applications.

camso.co

PERFORMANCE

TIRE LIFE



PUNCTURE RESISTANCE



TRACTION



CAMSO SKS 793S



INNOVATIVE NON-DIRECTIONAL TREAD PATTERN

- Provides greater durability and versatility for mixed and hard surface applications

REUSABLE WHEEL

- Provides lower cost per hour and quicker installation



NEW ELONGATED APERTURE DESIGN

- Provides excellent ride quality and reduces cracking

MASSIVE TREAD DEPTH

- Improves durability for longer service life

TIRE SIZE	RIM SIZE	ACTUAL TIRE DIMENSIONS			HEEL		LOAD CAPACITY [kg] [lb]							
							Counterbalanced lift trucks				Other vehicles			Static
							Load wheel		Steering wheel					
		15 km/h 9 mph	25 km/h 16 mph	25 km/h 16 mph	6 km/h 4 mph	10 km/h 6 mph	25 km/h 16 mph	0 km/h 0 mph						
O.D. [mm] [in]	O.W. [mm] [in]	O.T.D. [mm] [32nd]	Normal	Quick										
23x8-12 (23x8.50-12)	5.00S	573	190	19	-	■	-	2910	2240	2910	2645	2240	3380	
		22.6	7.5	24			-	6415	4940	6415	5830	4940	7450	
5.70-13 (5.70-12)	3.75P	570	133	20	-	■	-	2015	1550	2015	1830	1550	2340	
		22.4	5.2	25			-	4440	3415	4440	4035	3415	5160	
27x8.50-16 (27x8.50-15)	5.50	676	187	25	-	■	-	3350	2575	3350	3040	2575	3890	
		26.6	7.4	31			-	7385	5675	7385	6700	5675	8575	
31x10-20 (10-16.5)	7.50	780	233	39	-	■	-	4030	3100	4030	3660	3100	4680	
		30.7	9.2	49			-	8885	6835	8900	8100	6850	10350	
33x12-20 (12-16.5)	7.50	830	285	43	-	■	-	5200	4000	5200	4720	4000	6040	
		32.7	11.2	54			-	11465	8820	11500	10400	8850	13350	
36x14-20 (14-17.5)	7.50	910	322	52	-	■	-	6175	4750	6175	5605	4750	7175	
		35.8	12.7	66			-	13650	10500	13650	12350	10500	15850	

